


Supplier's name or trade mark:		Coen Bakker Deco B.V.		
Supplier's address:		Smeetsweg 4a 1738 DK WAARLAND NETHERLANDS		
Model identifier:		240336		
Type of light source:		Led tree with star		
Lighting technology used:	LED	Led qty	236pcs	
Led type:	4mm micro LED leather coated	Input voltage	220-240V	
Power supply mode	DC adapter	Output voltage	5V	
Dimming or not:	Yes	Timing or not	8Hours on, 16Hours off	
High luminance light source:	no	Connected light source (CLS):	no	
Anti-glare shield:	no	Output current	2000mA	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer:	10kWh/1 000 h	Energy efficiency class:		
Useful luminous flux (Φ_{lm}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°):	180 lumen in a wide cone (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:	[2000K]	
On-mode power (P_{on}), expressed in W:	10W	Standby power (P_{st}), expressed in W and rounded to the second decimal:	0	
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal:	/	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set:	[60]	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	Height:	2000mm	Spectral power distribution in the range 350 nm to 1000 nm, at full-load: 	
	Width:			700mm
	Depth:			700mm
Claim of equivalent power	Yes	If yes, equivalent power (W)	0,06	
		Chromaticity coordinates (x and y):	X:0.2436 y:0.2187	
Parameters for directional light sources:				
Peak luminous intensity (cd):	/	Beam angle in degrees, or the range of beam angles that can be set:	[180]	
Parameters for LED and OLED light sources:				
R9 colour rendering index value:	1	Survival factor:	0,80	
the lumen maintenance factor:	0,8			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ):	0,50	Colour consistency in McAdam ellipses:	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.:	[NO]	If yes then replacement claim (W) /		
Flicker metric (Pst LM):	≤1.0	Stroboscopic effect metric (SVM):	≤0.4	