


|                                                                                                                                                |                                             |                                                                                                                                                             |                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Supplier's name or trade mark:                                                                                                                 |                                             | Coen Bakker Deco B.V.                                                                                                                                       |                                                                                       |
| Supplier's address:                                                                                                                            |                                             | Smeetsweg 4a 1738 DK WAARLAND NETHERLANDS                                                                                                                   |                                                                                       |
| Model identifier:                                                                                                                              |                                             | 261289                                                                                                                                                      |                                                                                       |
| Type of light source: Led string light                                                                                                         |                                             |                                                                                                                                                             |                                                                                       |
| Lighting technology used:                                                                                                                      | LED                                         | Led qty                                                                                                                                                     | 1200pcs                                                                               |
| Led type:                                                                                                                                      | SMD 0603 SMD0805                            | Input voltage                                                                                                                                               | 220-240V                                                                              |
| Power supply mode                                                                                                                              | DC adapter                                  | Output voltage                                                                                                                                              | 12V                                                                                   |
| Dimming or not:                                                                                                                                | Yes                                         | Timing or not                                                                                                                                               | Yes                                                                                   |
| High luminance light source:                                                                                                                   | no                                          | Connected light source (CLS):                                                                                                                               | no                                                                                    |
| Anti-glare shield:                                                                                                                             | no                                          | Output current                                                                                                                                              | 500mA                                                                                 |
| <b>Product parameters</b>                                                                                                                      |                                             |                                                                                                                                                             |                                                                                       |
| Parameter                                                                                                                                      | Value                                       | Parameter                                                                                                                                                   | Value                                                                                 |
| <b>General product parameters:</b>                                                                                                             |                                             |                                                                                                                                                             |                                                                                       |
| Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer:                                                                | 6kWh/1 000 h                                | Energy efficiency class:                                                                                                                                    | G                                                                                     |
| Useful luminous flux ( $\Phi_{uv}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°): | 125 lumen in a wide cone (360°)             | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set: | [2642K]                                                                               |
| On-mode power ( $P_{on}$ ), expressed in W:                                                                                                    | 6W                                          | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal:                                                                               | 0                                                                                     |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal:                                               | /                                           | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set:                                                         | [60]                                                                                  |
| Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):                    | Height: 105mm<br>Width: 40mm<br>Depth: 35mm | Spectral power distribution in the range 250 nm to 800 nm, at full-load:                                                                                    |  |
| Claim of equivalent power                                                                                                                      | Yes                                         | If yes, equivalent power (W)                                                                                                                                | 0,06                                                                                  |
|                                                                                                                                                |                                             | Chromaticity coordinates (x and y):                                                                                                                         | X:0.47<br>y:0.42                                                                      |
| <b>Parameters for directional light sources:</b>                                                                                               |                                             |                                                                                                                                                             |                                                                                       |
| Peak luminous intensity (cd):                                                                                                                  | /                                           | Beam angle in degrees, or the range of beam angles that can be set:                                                                                         | [120]                                                                                 |
| <b>Parameters for LED and OLED light sources:</b>                                                                                              |                                             |                                                                                                                                                             |                                                                                       |
| R9 colour rendering index value:                                                                                                               | 1                                           | Survival factor:                                                                                                                                            | 0,80                                                                                  |
| the lumen maintenance factor:                                                                                                                  | 0,8                                         |                                                                                                                                                             |                                                                                       |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                                        |                                             |                                                                                                                                                             |                                                                                       |
| displacement factor ( $\cos \phi$ ):                                                                                                           | 0,50                                        | Colour consistency in McAdam ellipses:                                                                                                                      | 6                                                                                     |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.:                       | [NO]                                        | If yes then replacement claim (W) /                                                                                                                         |                                                                                       |
| Flicker metric (Pst LM):                                                                                                                       | $\leq 1.0$                                  | Stroboscopic effect metric (SVM):                                                                                                                           | $\leq 0.4$                                                                            |