REGULATION (EU) 2019/2015
Annex V, Table 3
Product Information sheet

Supplier' s name or trade mark:		**Coen Bakker Deco B.V.**	
Supplier' s address:		**Smeetsweg 4a 1738 DK WAARLAND NETHERLANDS**	
Model identifier:		**261253**	
Type of light source:		**Led string light**	
Lighting technology used:	LED	Led qty	800pcs
Led type:	SMD 0603 SMD0805	Input voltage	220-240V
Power supply mode	DC adapter	Output voltage	12V
Dimming or not:	Yes	Timing or not	Yes
High luminance light source:	no	Connected light source (CLS):	no
Anti-glare shield:	no	Output current	500MA
Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer:	6kWh/1 000 h	Energy efficiency class :	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) :	125 lumen in a wide cone (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set :	[2024K]
On-mode power (P_{on}), expressed in W :	6W	Standby power (P_{sb}), expressed in W and rounded to the second decimal:	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal :	/	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set:	[60]
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre): Height:	105mm	Spectral power distribution in the range 250 nm to 800 nm, at full-load:	
Width:	40mm		
Depth:	35mm		
Claim of equivalent power	Yes	If yes, equivalent power (W)	0,06
		Chromaticity coordinates (x and y):	X:0.54 y:0.43
Parameters for directional light sources:			
Peak luminous intensity (cd) :	/	Beam angle in degrees, or the range of beam angles that can be set:	[120]
Parameters for LED and OLED light sources:			
R9 colour rendering index value :	1	Survival factor:	0,80
the lumen maintenance factor :	0,8		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1) :	0,50	Colour consistency in McAdam ellipses:	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. :	[NO]	If yes then replacement claim (W)	/
Flicker metric (Pst LM) :	≦1.0	Stroboscopic effect metric (SVM):	≦0.4