


Supplier's name or trade mark:		Coen Bakker Deco B.V.		
Supplier's address:		Smeetsweg 4a 1738 DK WAARLAND NETHERLANDS		
Model identifier:		261317		
Type of light source:		Led string light		
Lighting technology used:	LED	Led qty	500pcs	
Led type:	SMD 0603	Input voltage	220-240V	
Power supply mode	DC adapter	Output voltage	6.5V	
Dimming or not:	Yes	Timing or not	Yes	
High luminance light source:	no	Connected light source (CLS):	no	
Anti-glare shield:	no	Output current	600MA	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer:	2kWh/1 000 h	Energy efficiency class:	G	
Useful luminous flux (Φ_{lm}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°):	125 lumen in a wide cone (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:	[1969K]	
On-mode power (P_{on}), expressed in W:	3.9W	Standby power (P_{sb}), expressed in W and rounded to the second decimal:	0	
Networked standby power (P_{sn}) for CLS, expressed in W and rounded to the second decimal:	/	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set:	[60]	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	Height:	105mm	Spectral power distribution in the range 250 nm to 800 nm, at full-load:	
	Width:			
	Depth:			
Claim of equivalent power	Yes	If yes, equivalent power (W)	0,06	
		Chromaticity coordinates (x and y):	X:0.53 y:0.43	
Parameters for directional light sources:				
Peak luminous intensity (cd):	/	Beam angle in degrees, or the range of beam angles that can be set:	[120]	
Parameters for LED and OLED light sources:				
R9 colour rendering index value:	1	Survival factor:	0,80	
the lumen maintenance factor:	0,8			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ):	0,50	Colour consistency in McAdam ellipses:	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.:	[NO]	If yes then replacement claim (W)	/	
Flicker metric (Pst LM):	$\leq 1,0$	Stroboscopic effect metric (SVM):	$\leq 0,4$	

